Last DSM Input Bit List 1st November 2004

Input Channel	Bit Description
0	CTB Multiplicity Bits 0:15 – Multiplicity
1	VTX Information
1	Bit 0 – BBC TAC difference in window
	Bit 1 – ZDC TAC difference in window
	Bit 2 – BBC East small-tile ADC sum over threshold
	Bit 3 – BBC West small-tile ADC sum over threshold
	Bit 4 – BBC East large-tile ADC sum over threshold
	Bit 5 – BBC West large-tile ADC sum over threshold
	Bit 6 – ZDC East ADC sum over threshold 0
	Bit 7 – ZDC West ADC sum over threshold 0
	Bit 8 – ZDC East TAC in window
	Bit 9 – ZDC West TAC in window
	Bit 10 – ZDC East+West attenuated sum over threshold
	Bit 11:13 – Unused
	Bit 14 – ZDC East ADC sum over threshold 1
2	Bit 15 – ZDC West ADC sum over threshold 1 Other CTB Information
2	Bits 0:13 – Unused
	Bit 14 – Topology flag (i.e. no hits on the top or bottom of the
	CTB and a few hits representing 2-prong events). The topology
	flag can be vetoed by the presence of either out-of-time hits or an
	overflow. The veto configuration is set up using a register in the
	CB201 DSM.
	Bit 15 – LED flag
3	EMC Information
	Bits 0:1 – Barrel jet patch bits encoding which of 3 thresholds is
	passed
	Bits 2:3 – Barrel high-tower bits encoding which of 3 thresholds
	is passed
	Bit 4 - Unused
	Bit $5 - J/\Psi$ topology flag (i.e. 2 opposite jet patches have high
	towers over a threshold, presently just west half of barrel). Bit 6 – Jet patch topology flag (i.e. a pair of adjacent jet patches
	have energies over a threshold, either barrel or endcap).
	Bits 7:8 – Endcap jet patch bits encoding which of 3 thresholds is
	passed
	Bits 9:10 – Endcap high-tower bits encoding which of 3
	thresholds is passed
	Bits 11:15 – Unused
4	Miscellaneous Information from Scaler Source Patch Panel
	Bit 0 – Blue bunch filled
	Bit 1 – Yellow bunch filled
	Bits 2:15 - Unknown
5	FPD
	Bit 0 – FPD East bit.
	If the sum algorithms have been used then this bit means the
	ADC sum was over threshold. A register in the FP201 DSM is
	used to select which 1 of 3 available threshold comparisons is

	used to make this bit.
	If the high-tower algorithms have been used then this bit means at
	least one PMT produced a signal over a threshold. As with the
	sum algorithms, a register in the FP201 DSM is used to select
	which 1 of 3 available threshold comparisons is used to make this
	bit.
	Bit 1 – FPD West bit.
	The selected threshold is the same one selected for the East side.
	Bits 2:15 - Unused
6	Special Trigger Requests
	Bits 0:2 – selected special trigger request (zero if no request)
	Bits 3:6 – detector number (0:15) of detector making request
	Bits 7:13 – Unused
	Bit 14 – Zero-bias bit
	Bit 15 – Random bit
7	Unused